



True to its thoroughbred form, the Bombardier' Learjet' 60 XR completely outpaces the competition in time-to-climb performance and operating altitude without compromising a class-leading low operating cost. With its cutting-edge cockpit technologies and stylishly redefined cabin space, the Learjet 60 XR business jet speeds passengers across distances of up to 2,338 nautical miles (4,330 km) with ease.

- Class-leading low operating cost
- Rethought, redesigned interior provides passengers with more space and better cabin functionality
- 'Next-generation' flight deck design and technologies led by the Rockwell Collins Pro Line 21 avionics suite

#### **GENERAL**

### Capacity

Crew: 2

Passengers: Up to 8 + 1

#### **Engines**

Pratt & Whitney Canada PW305A turbofans

Thrust: 4,600 lb (20.46 kN) Flat rated to: ISA + 17°C (90°F)

#### **Avionics**

- All-digital Rockwell Collins Pro Line 21 four LCD EFIS
- Dual automatic Attitude Heading Reference System (AHRS)
- Digitized Engine Indication System (EIS)
- Integrated Flight Instrument System (IFIS) with electronic charts
- WXR 840 weather radar
- Dual nav/comm systems
- Dual Flight Management System (FMS)
- Traffic Collision Avoidance System (TCAS II)
- Enhanced Ground Proximity Warning System (EGPWS) with Windshear alert
- Emergency Locator Transmitter (ELT)

#### PERFORMANCE

#### Range

Maximum range: 2,338 NM 2,691 SM 4,330 km (NBAA IFR 100 NM reserves, ISA, with 4 pax/2 crew)

Mach kt mph km/h Speed High-speed 0.81 466 536 863 Typical cruise speed 0.79 453 521 839 Long-range speed 0.74 426 491 789

#### Airfield Performance

Takeoff distance (SL, ISA, MTOW): 5,450 ft (1,661 m)

Landing distance (SL, ISA, MLW): 3,420 ft (1,042 m)

#### **Operating Altitude**

Maximum operating altitude: 51,000 ft (15,545 m)

Climb to cruise altitude of 41,000 ft (12,497 m) after MGTOW departure: 18 min, 30 sec

#### Noise Level (EPNdB)

Flyover (thrust cutback): 70.8

Approach: 87.7 Lateral: 83.2

## DIMENSIONS

#### Exterior

Length: 58.69 ft (17.89 m) Wingspan: 43.79 ft (13.35 m) Wing area: 264.5 ft² (24.57 m²)

(basic)

Height overall: 14.56 ft (4.44 m)

#### Interior

Cabin length: 17.67 ft (5.39 m) (from cockpit divider to end of pressurized compartment)

Cabin width: 5.95 ft (1.81 m)

(centerline)

Cabin width: 3.80 ft (1.16 m)

(floorline)

Weights

Cabin height: 5.71 ft (1.74 m)

Floor area: 69 ft<sup>2</sup> (6.41 m<sup>2</sup>) (excluding cockpit)

Cabin volume: 453 ft<sup>3</sup> (12.83 m<sup>3</sup>) (from cockpit divider to end


# of pressurized compartment)

- A. Maximum ramp weight: 23,750 lb (10,773 kg)
- B. Maximum takeoff weight: 23,500 lb (10,659 kg)
- C. Maximum landing weight: 19,500 lb (8,845 kg)
- D. Maximum zero fuel weight: 17,000 lb (7,711 kg)
- E. Typical basic operating weight: 15.081 lb (6.841 kg)
- F. Maximum fuel weight: 7,910 lb (3,588 kg)

Maximum payload (D-E): 1,919 lb (870 kg)

Payload – maximum fuel (A-E-F): 759 lb (344 kg)

Fuel with maximum payload: 6,750 lb (3,062 kg)



Bombardier Aerospace, Business Aircraft, 400 Côte-Vertu Road West, Dorval, Québec, Canada H4S 1Y9 In North America call 800-268-0030 • Elsewhere call 514-855-7698 • www.businessaircraft.bombardier.com

Performance is based on maximum takeoff/landing weight, sea level, standard day (ISA) conditions, unless otherwise noted. All data in this document is approximate, for discussion purposes only and may be subject to certain conditions. This document does not constitute an offer, commitment, representation or warranty of any kind. All data is subject to change without prior notice. The interior images shown are for information purposes only and may represent some optional configurations. The final configuration and performance of the aircraft shall be as per the contractually agreed upon purchase agreement.

©2008 Bombardier Inc. All rights reserved. \* Registered Trademark(s) or Trademark(s) of Bombardier Inc. or its subsidiaries. Printed in Canada (07/08).

**BOMBARDIER**